FORTICETM PENDANT

PROJECT:	
TYPE:	





PN: 6465

WEIGHT

1 14. OTO	<u> </u>
ILLUMINATION	7,561 - 29,929 LUMENSDIFFUSELED 90CRI
APPLICATION	PENDANT MOUNTRATED: INDOOR
DIMENSION	 24", 36", 48", 60", AND 72" DIA. (61cm, 91cm, 122cm, 152cm, and 183cm) PROFILE: 4.31"W X 2.75"H (11cm X 7cm)
ELECTRICAL	• 120 - 277V • 10KV SURGE SUPRESSION
DIFFUSERS	HIGH EFFICIENCY ACRYLIC
MOUNTING	 120" (305cm) BLACK OR WHITE DROP CORD WITH AC CABLES 120" POWER OVER SUSPENSION
LED DRIVER	CANOPY OR REMOTE MOUNT
CONSTRUCTION	• ALUMINUM
FINISHES	 AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES CUSTOM RAL FINISHES AVAILABLE
DIMMING	 0 - 10V (1%) DIMMING (120-277V) LINE VOLTAGE/TRIAC/ELV (120V ONLY) LUTRON HI-LUME (1%) DIMMING (120-277V)

• 25 LBS MINIMUM, 45 LBS MAXIMUM





DIFFUSE



FORTICETM PENDANT

PROJECT: .	
TYPE:	
QUANTITY:	
QUANTITI	

6465							
	1	2	3	4	5	6	7

1.	24	36	48	60	72
SIZE	24" (61CM)	36" (91CM)	48" (122CM)	60" (152CM)	72" (183CM)
LED (W)	76W	132W	189W	252W	303W
LUMENS	7561	13129	18745	24960	29929

2.	H M		L	C:	
OUTPUT	100% LUMENS	75% LUMENS	50% LUMENS	[CUSTOM]% LUMENS	

3.	30К	35K	40K
CCT	3000	3500	4000


4.	MMCD	MMRM	PSCD	PSRM	
MOUNTING	MULTIPLE CABLES WITH CANOPY DRIVER	MULTIPLE CABLES WITH REMOTE DRIVER	SINGLE POINT WITH CANOPY DRIVER	SINGLE POINT WITH REMOTE DRIVER	

5.	BC	wc	POS
CORD	BLACK DROP CORD WITH AIRCRAFT CABLES	WHITE DROP CORD WITH AIRCRAFT CABLES	POWER OVER SUSPENSION (SILVER ONLY) (IVP TO 60° ONLY) (NOT APPLICABLE FOR MMCD COMBINATION)

6.	ADDITIONAL AND PREMIUM FINISHES	F04	F05	F15	F16	F09	F31	F18
FINISH	AVAILABLE. SEE FINISHES CHART	MATTE WHITE	GLOSS WHITE	MATTE BLACK	GLOSS BLACK	PEWTER	SILVER METALLIC	SATIN ALUMINUM

7.	DIML	DIME	DIMV	
DIMMING	0-10V (1%) (120-277V)	LUTRON HI-LUME (1%) (120-277V) (UP TO 36° ONLY)	LINE VOLTAGE/TRIAC/ELV (120V ONLY)	

FORTICE™ PENDANT





SIZES	DIAMETER	MOUNTING		CANOF	Y SIZE	NUMBER	WEIGHT	SECTIONS
SIZES	DIAMETER	POINT	WINININION DISTANCE	MMCD	PSCD - PSRM	OF CANOPY	(POUNDS - LBS)	SECTIONS
24	24"	3	19"	9.4"	10.5"	1	25	1
36	36"	3	35"	10.25"	10.5"	1	30	1
48	48"	3	46"	15"	15"	1	35	1
60	60"	4	62"	15"	15"	1	40	1
72	72"	4	79"	15"	15"	1	45	1

1.0NLY FOR PS (SINGLE POINT) MOUNTING OPTION, THIS IS THE MINIMUM DISTANCE FROM CEILING TO THE BOTTOM OF THE FIXTURE 2.MINIMUM CABLE MOUNTING ANGLE IS 70°


POS (POWER OVER SUSPENSION)


MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)







PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)






PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)







DROP CORD


MMCD COMBINATION (MUTIPLE CABLES, CANOPY MOUNT DRIVER)







MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)







PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)





PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)





FORTICETM PENDANT

DIFFUSE


PN	SIZE (LENGTH)	LUMENS	WATTAGE
	24	7561	76
	36	13129	132
6465	48	18745	189
	60	24960	252
	72	29929	303


IES INDOOR REPORT

PHOTOMETRIC FILENAME: 6465 24 ID 35K F05.IES

POLAR GRAPH


IES INDOOR REPORT





TOTAL LUMINAIRE EFFICIENCY LUMINAIRE EFFICACY RATING TOTAL LUMINAIRE WATTS

IGLE = 90, VERTICAL ANGLE = 5 270) (THROUGH MAX. CD.) ROUGH MAX. CD.)	MAXIMUM CANDELA = 2795.82 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 20 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD.) # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (20) (THROUGH MAX. CD.)		
7561	LUMINAIRE LUMENS	29929	
80%	TOTAL LUMINAIRE EFFICIENCY	80%	
100	LUMINAIRE EFFICACY RATING	99	
76	TOTAL LUMINAIRE WATTS	303	



PHOTOMETRIC FILENAME: 6465 72 ID 35K F05.IES

FORTICE™ PENDANT

FINISHES



F04 MATTE WHITE



F05 GLOSS WHITE



F15 MATTE **BLACK**



F16 GLOSS BLACK



F09 **PEWTER**



F31 SILVER METALLIC



F18 SATIN ALUMINUM



F21 ARCH **BRONZE**

PREMIUM FINISHES



RAL CUSTOM (RAL #)



F40 **BUBBLE PINK**



F10 FIRE **RED**



F41 **ELECTRIC PURPLE**



F08 **MIDNIGHT BLUE**



F39 AQUA BĽUE



F13 **FOREST GREEN**



F38 MEADOW GREEN



F45 **COPPER** METALLIC



F06 CLAY **BROWN**



F11 **CITRUS ORANGE**



F28 DARK **CHAMPAGNE**



F22 HARVEST **GOLD**



F14 SUNSHINE YELLOW



F33 **PYRITE BRONZE**



F07 **ZEUS BROWN**



F32 **BRONZE** METALLIC



F26 **MELTED COPPER**



F25 **MELTED** GOLD



F24 **MELTED**



F44 **FAUX** COPPER



F43 **FAUX** GOLD



F42 **FAUX** CHROME

PLATINUM