

LUNA ACOUSTIC™ PENDANT


PROJECT:	
TYPE:	
OLIA NITITY.	




PN: 971LU

ILLUMINATION	3101 - 12,185 LUMENSDIRECT OR INDIRECT/DIRECTLED 90CRI
APPLICATION	DIRECT OR DIRECT/INDIRECT PENDANT MOUNTINDOOR RATED
DIMENSION	 24", 36", 48" DIA. (61cm, 91cm, and 122cm) PROFILE: 1"W X 2.625"H (2.5cm X 6.6cm)
ELECTRICAL	120 - 277V10KV SURGE SUPRESSION
DIFFUSERS	HIGH EFFICIENCY ACRYLIC
MOUNTING	 120" (305cm) BLACK OR WHITE DROP CORD WITH AC CABLES 120" POWER OVER SUSPENSION
LED DRIVER	CANOPY OR REMOTE MOUNT
CONSTRUCTION	• ALUMINUM
FINISHES	 AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES CUSTOM RAL FINISHES AVAILABLE
DIMMING	 0 - 10V (1%) DIMMING (120-277V) LINE VOLTAGE/TRIAC/ELV (120V ONLY) LUTRON HI-LUME (1%) DIMMING (120-277V)
WEIGHT	• 16 LBS MINIMUM, 34 LBS MAXIMUM









PROJECT:	
TYPE:	
OUANTITY:	
Q 07	

1.	DIRECT						
DIAMETER	24D		36	SD .		48D	
(INCH)	24" (61CM)		36" (9	91CM)		48" (122CM)	
LED (W)	34W		51	.W		68W	
LUMENS	3101		4608		6158		
	INDIRECT/DIRECT						
DIAMETER	24ID		36	iD		48ID	
(INCH)	24" (61CM)		36" (91CM)			48" (122CM)	
LED (W)	68W		10	2W		136W	
LUMENS	6104		9091			12185	
2.	Н		М	L		C:1	

OUTPUT	100% LUMENS	75% LUMENS		50% LUMENS		[CUSTOM]% LUMENS	
3.	30К		35К		40к		
CCT	3000К		3500K		4000К		

4.	S	D
CIRCUIT	SINGLE	DUAL

5.	MMCD	MMRM	PSCD	PSRM
MOUNTING	MULTIPLE CABLES WITH CANOPY DRIVER	MULTIPLE CABLES WITH REMOTE DRIVER	SINGLE POINT WITH CANOPY DRIVER	SINGLE POINT WITH REMOTE DRIVER

6.	BC	wc	POS
CORD	BLACK DROP CORD WITH AIRCRAFT CABLES	WHITE DROP CORD WITH AIRCRAFT CABLES	POWER OVER SUSPENSION (SILVER ONLY) (NOT APPLICABLE FOR MMCD COMBINATION)

7.	FLAT	DOM
DIFFUSER	FLAT DIFFUSER	DOME DIFFUSER


8.	C	w	MA	CA	RH	SG	HG	СН
	COCONU	IT WHITE	MARBLE	CAPPUCCINO	RHINO GREY	STEEL GREY	HEATHER GREY	CHARCOAL
ACOUSTIC COLOR	TA	RR	MT	GG	GA	LB	DO	CG
	TANGERINE	RUBY RED	MANGO TWIST	GOLF GREEN	GREEN APPLE	LINEN BLUE	DEEP OCEAN	CYBER GRAPE


9.	ADDITIONAL AND PREMIUM FINISHES	F04	F05	F15	F16	F09	F31	F18
FINISH	AVAILABLE. SEE FINISHES CHART	MATTE WHITE	GLOSS WHITE	MATTE BLACK	GLOSS BLACK	PEWTER	SILVER METALLIC	SATIN ALUMINUM


10.	DIML	DIML DIME	
DIMMING	0-10V (1%) (120-277V)	LUTRON HI-LUME (1%) (120-277V)	LINE VOLTAGE/TRIAC/ELV (120V ONLY)

^{1.} CUSTOM PERCENTAGE I.E. 60%. CONSULT FACTORY.









24D / 24ID

36D / 36ID


48D / 48ID


SIZES	DIAMETER	MOUNTING POINT	MINIMUM DISTANCE ¹²	CANOPY SIZE		NUMBER	WEIGHT	SECTIONS
SIZES	DIAMETER			MMCD	PSCD - PSRM	OF CANOPY	(POUNDS - LBS)	SECTIONS
24	24"	3	30"	10"	12"	1(D)/ 1(ID)	16(D)/ 18(ID)	1
36	36.5"	3	42"	10"	12"	1(D)/ 1(ID)	22(D)/ 24(ID)	1
48	47.5"	3	54"	12"	15"	1(D)/ 1(ID)	32(D)/ 34(ID)	1
4 ONLY FOR DO CONCLE POINT MOUNTING OPTION, THIS IS THE MINIMUM DISTANCE FROM OF THE FIXTURE								

1.0NLY FOR PS (SINGLE POINT) MOUNTING OPTION, THIS IS THE MINIMUM DISTANCE FROM CEILING TO THE BOTTOM OF THE FIXTURE 2.MINIMUM CABLE MOUNTING ANGLE IS 70°


POS (POWER OVER SUSPENSION)

MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)






PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)






PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)







DROP CORD


MMCD COMBINATION (MUTIPLE CABLES, CANOPY MOUNT DRIVER)






MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)






PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)





PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)






DIRECT

PN	SIZE (DIA)	LUMENS	WATTAGE	WEIGHT
	24D	3101	34	16 LBS
971LU	36D	4608	51	22 LBS
	48D	6158	68	32 LBS

IES INDOOR REPORT

PHOTOMETRIC FILENAME: 947LU 24D CH 35K F16.IES

POLAR GRAPH



MAXIMUM CANDELA = 1172.49 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 0 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD) # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (0) (THROUGH MAX. CD)

LUMINAIRE LUMENS
TOTAL LUMINAIRE EFFICIENCY
LUMINAIRE EFFICACY RATING
TOTAL LUMINAIRE WATTS


INDIRECT / DIRECT

PN	SIZE (DIA)	LUMENS	WATTAGE	WEIGHT
	24D	6104	68	18 LBS
971LU	36D	9091	102	24 LBS
	48D	12185	136	34 LBS

IES INDOOR REPORT

PHOTOMETRIC FILENAME: 947LU 48D CH 35K F16.IES

POLAR GRAPH



MAXIMUM CANDELA = 1838.81 LOCATED AT HORIZONTAL ANGLE = 180, VERTICAL ANGLE = 5 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (180 - 0) (THROUGH MAX. CD) # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (5) (THROUGH MAX. CD)

LUMINAIRE LUMENS	12185
TOTAL LUMINAIRE EFFICIENCY	71%
LUMINAIRE EFFICACY RATING	90
TOTAL LUMINAIRE WATTS	135

FINISHES



F04 MATTE WHITE



F05 **GLOSS** WHITE



F15 **MATTE BLACK**



F16 **GLOSS BLACK**



F09 **PEWTER**



F31 **SILVER METALLIC**



F18 SATIN **ALUMINUM**



F21 **ARCH BRONZE**

PREMIUM FINISHES



RAL CUSTOM (RAL #)



F40 **BUBBLE PINK**



F10 **FIRE** RED



F41 **ELECTRIC PURPLE**



F08 **MIDNIGHT BLUE**



F39 **AQUA** BĽUE



F13 **FOREST GREEN**



F38 **MEADOW GREEN**



F45 **COPPER METALLIC**



F06 CLAY **BROWN**



F11 **CITRUS** ORANGE



F28 DARK CHAMPAGNE



F22 HARVEST GOLD



F14 SUNSHINE YELLOW



F33 **PYRITE BRONZE**



F07 **ZEUS BROWN**



F32 BRONZE METALLIC



F26 MELTED COPPER



F25 **MELTED GOLD**



F24 MELTED PLATINUM



F44 **FAUX COPPER**



F43 **FAUX GOLD**



F42 **FAUX CHROME**

ACOUSTIC COLORS



NOTE: DISPLAYED FINISHES DIFFER BETWEEN SCREENS AS WELL AS PRINTERS AND MAY NOT ACCURATELY DEPICT COLOR.