

LUNA FUSO L™ PENDANT

PROJECT: _____

TYPE: _____


QUANTITY: _____





PN: 871LU03

ILLUMINATION	<ul style="list-style-type: none"> • 10,743 - 21,346 LUMENS • DIRECT OR INDIRECT/DIRECT • LED 90CRI
APPLICATION	<ul style="list-style-type: none"> • DIRECT OR DIRECT/INDIRECT PENDANT MOUNT • INDOOR RATED
DIMENSION	<ul style="list-style-type: none"> • 24" SIZE (61cm) • PROFILE: 1"W X 2.625"H (2.54cm X 6.6675cm)
ELECTRICAL	<ul style="list-style-type: none"> • 120 - 277V • 10KV SURGE SUPPRESSION
DIFFUSERS	<ul style="list-style-type: none"> • HIGH EFFICIENCY ACRYLIC
MOUNTING	<ul style="list-style-type: none"> • 120" (304.8cm) BLACK OR WHITE DROP CORD WITH AIRCRAFT CABLES • 120" (304.8cm) POWER OVER SUSPENSION
LED DRIVER	<ul style="list-style-type: none"> • CANOPY OR REMOTE MOUNT
CONSTRUCTION	<ul style="list-style-type: none"> • ALUMINUM
FINISHES	<ul style="list-style-type: none"> • AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES • CUSTOM RAL FINISHES AVAILABLE
DIMMING	<ul style="list-style-type: none"> • 0 - 10V (1%) DIMMING (120-277V) • LINE VOLTAGE/TRIAC/ELV (120V ONLY) • LUTRON HI-LUME (1%) DIMMING (120-277V)
WEIGHT	<ul style="list-style-type: none"> • 30 LBS MINIMUM, 56 LBS MAXIMUM

FLAT DIFFUSER



DOM DIFFUSER



LUNA FUSO L™ PENDANT




PROJECT: _____

TYPE: _____

QUANTITY: _____


871LU03



1.	DIRECT							
SIZE	242D 83"L X 48"W (211CM X 122CM)							
LED (W)	119W							
LUMENS	10743							
	INDIRECT / DIRECT							
SIZE	242ID 83"L X 48"W (211CM X 122CM)							
LED (W)	237W							
LUMENS	21346							
2.	H	M	L	C: _____				
OUTPUT	100% LUMENS	75% LUMENS	50% LUMENS	[CUSTOM]% LUMENS				
3.	30K		35K			40K		
CCT	3000		3500			4000		
4.	S				D			
CIRCUITS	SINGLE				DUAL			
5.	MMCD				MMRM			
MOUNTING	MULTIPLE CABLES AND CANOPY DRIVER				MULTIPLE CABLES AND REMOTE DRIVER			
6.	BC				WC			
CORD	BLACK DROP CORD WITH AIRCRAFT CABLES				WHITE DROP CORD WITH AIRCRAFT CABLES			
7.	FLAT				DOM			
DIFFUSER	FLAT DIFFUSER				DOME DIFFUSER			
8.	ADDITIONAL AND PREMIUM FINISHES AVAILABLE. SEE FINISHES CHART	F04	F05	F15	F16	F09	F31	F18
FINISH		MATTE WHITE	GLOSS WHITE	MATTE BLACK	GLOSS BLACK	PEWTER	SILVER METALLIC	SATIN ALUMINUM
9.	DIML		DIME			DIMV		
DIMMING	0-10V (1%) (120-277V)		LUTRON HI-LUME (1%) (120-277V)			LINE VOLTAGE/TRIAC/ELV (120V ONLY)		

NOTE: SOME OPTIONS MAY NOT BE COMPATIBLE WITH OTHERS. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT TMS LIGHTING FOR UPDATED SPECIFICATIONS.

LUNA FUSO L™ PENDANT





SIZE	ACTUAL SIZE	MOUNTING POINTS	CANOPY SIZE	NUMBER OF CANOPY	WEIGHT (POUNDS - LBS)	SECTIONS
242	48"W x 83"L	6	15"	1(D)/ 1(ID)	56	1



LUNA FUSO L™ PENDANT

DROP CORD

MMCD COMBINATION (MULTIPLE CABLES, CANOPY MOUNT DRIVER)



MMRM COMBINATION (MULTIPLE CABLES, REMOTE MOUNT DRIVER)



LUNA FUSO L™ PENDANT


DIRECT

PN	LUMENS	WATTAGE
87LU03	10743	118

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 871LU03-84-D-35K-F05.IES

POLAR GRAPH



MAXIMUM CANDELA = 3893.9 LOCATED AT HORIZONTAL ANGLE = 90, VERTICAL ANGLE = 5
 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) (THROUGH MAX. CD.)
 # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (5) (THROUGH MAX. CD.)

LUMINAIRE LUMENS
 TOTAL LUMINAIRE EFFICIENCY
 LUMINAIRE EFFICACY RATING
 TOTAL LUMINAIRE WATTS

10743
 71%
 91
 119


INDIRECT / DIRECT

PN	LUMENS	WATTAGE
87LU03	21346	237

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 871LU03-84-ID-35K-F05.IES

POLAR GRAPH



MAXIMUM CANDELA = 3889.18 LOCATED AT HORIZONTAL ANGLE = 67.5, VERTICAL ANGLE = 5
 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (65.7 - 247.5) (THROUGH MAX. CD.)
 # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (5) (THROUGH MAX. CD.)

LUMINAIRE LUMENS
 TOTAL LUMINAIRE EFFICIENCY
 LUMINAIRE EFFICACY RATING
 TOTAL LUMINAIRE WATTS

21346
 71%
 90
 237

LUNA FUSO L™ PENDANT

FINISHES



PREMIUM FINISHES



NOTE: DISPLAYED FINISHES DIFFER BETWEEN SCREENS AS WELL AS PRINTERS AND MAY NOT ACCURATELY DEPICT COLOR.