# LUNA QUDO<sup>TM</sup> PENDANT

PROJECT: \_


#### TYPE:

QUANTITY: \_



### PN: 941LUQP

ILLUMINATION	<ul> <li>2,843 - 19,475 LUMENS</li> <li>DIRECT OR INDIRECT/DIRECT</li> <li>LED 90CRI</li> </ul>	1.0IN 12.5CM	1.0IN [2.5CM]
APPLICATION	<ul> <li>DIRECT OR DIRECT/INDIRECT PENDANT MOUNT</li> <li>INDOOR RATED</li> </ul>		
DIMENSION	<ul> <li>24", 36", 48", 60", 72", 84" SIZES (61cm, 92cm, 122cm, 153cm, 183cm, and 213cm</li> <li>PROFILE: 1"W X 2.625"H (2.54cm X 6.6675cm)</li> </ul>	2.6IN [6.7CM]	2.6IN [6.7CM]
ELECTRICAL	120 - 277V     10KV SURGE SUPRESSION		DIRECT ONLY
DIFFUSERS	HIGH EFFICIENCY ACRYLIC		
MOUNTING	<ul> <li>120" (304.8cm) BLACK OR WHITE DROP CORD WITH AIRCRAFT CABLES</li> <li>120" (304.8cm) POWER OVER SUSPENSION</li> </ul>	DOM DIFFUSER	1.0IN
LED DRIVER	CANOPY OR REMOTE MOUNT	[2.5CM]	[2.5CM]
CONSTRUCTION	ALUMINUM		
FINISHES	AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES     CUSTOM RAL FINISHES AVAILABLE	2.9IN [7.3CM]	2.9IN [7.3CM]
DIMMING	<ul> <li>0 - 10V (1%) DIMMING (120-277V)</li> <li>LINE VOLTAGE/TRIAC/ELV (120V ONLY)</li> <li>LUTRON HI-LUME (1%) DIMMING (120-277V)</li> </ul>		DIRECT ONLY
WEIGHT	• 17 LBS MINIMUM, 47 LBS MAXIMUM	INDINEOT-DINEOT	DIRECT ONE



## 



## TMSLIGHTING



DIML

0-10V (1%) (120-277V)

TMSLIGHTING

9.

DIMMING

1.

2D

LENGTH	20	3	U	40	50	0	J	10
LENGTH	24" (61cm)	36" (9	2cm)	48" (122cm)	60" (153cm)	72" (1	83cm)	
LED (W)	32W	48	W	65W	80W	96	W	
LUMENS	2843	42	64	5683	7096	82	8229	
	INDIRECT/DIRECT							
	2ID	31	D	4ID	5ID	61	D	7ID
LENGTH	24" (61cm)	36" (92cm)		48" (122cm)	60" (153cm)	72" (1	83cm)	84" (213cm)
LED (W)	64W	96	W	132W	160W	192W		224W
LUMENS	5478	82	96	11243	13926	16263		19475
2.	н			М	L	L C:		C:
OUTPUT	100% LUMENS 75% I		75% LUMENS	50% LUMENS [CI		[CU	JSTOM]% LUMENS	
3.	30	Ж		35К 40К			Ж	
LED CCT	3000 35			00		40	00	
4.	S D							
CIRCUITS	SINGLE				DU	AL		
5.	ММСД		MMRM	PSCD		PSRM		
MOUNTING	MULTIPLE CAB AND CANOPY DF			JLTIPLE CABLES REMOTE DRIVER	SINGLE POINT SIN WITH CANOPY DRIVER WITH R		SINGLE POINT I REMOTE DRIVER	
6.	В	С		w	WC POS		DS	

WHITE DROP CORD WITH AIRCRAFT CABLES

DIME

LUTRON HI-LUME (1%) (120-277V) (UP TO 48" ONLY)

F15

MATTE

BLACK

F16

GLOSS

BLACK

F05

GLOSS

WHITE

DIRECT



3D

## LUNA QUDO<sup>TM</sup> PENDANT

6D

7D

POWER OVER SUSPENSION (SILVER ONLY) (UP TO 60° ONLY) (NOT APPLICABLE FOR MMCD COMBINATION)

F31

SILVER

METALLIC

DIMV

LINE VOLTAGE/TRIAC/ELV (120V ONLY)

DOM

DOME DIFFUSER

F09

PEWTER

PROJECT: \_

TYPE:

5D

QUANTITY: \_

#### 

4D

NOTE: SOME OPTIONS MAY NOT BE COMPATIBLE WITH OTHERS. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT TMS LIGHTING FOR UPDATED SPECIFICATIONS.

F04

MATTE

WHITE



F18


SATIN


ALUMINUM


## **TMS**LIGHTING





	ACTUAL MOUNTING			CANOPY SIZE		NUMBER	WEIGHT	
SIZE	SIZE	POINTS	MINIMUM DISTANCE	MMCD	PSCD - PSRM	OF CANOPY	(POUNDS - LBS)	SECTIONS
24	24.5"	4	30"	10"	10"	1(D)/ 1(ID)	17	1
36	36.5"	4	50"	10"	10"	1(D)/ 1(ID)	21	1
48	48.5"	4	75"	10"	10"	1(D)/ 1(ID)	25	1
60	60.3"	4	90"	10"	10"	1(D)/ 1(ID)	37	1
72	72.3"	4	110"	12"	12"	1(D)/ 1(ID)	42	1
84	84"	4	N/A	12"	N/A	1(D)/ 1(ID)	47	1













— 36.0" – **3D / 3DI** 


36.0"

60.0"


# LUNA QUDO<sup>™</sup>PENDANT

### **POS (POWER OVER SUSPENSION)**

MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)





#### PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)





#### PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)











# LUNA QUDO<sup>TM</sup> PENDANT


### **DROP CORD**


#### MMCD COMBINATION (MUTIPLE CABLES, CANOPY MOUNT DRIVER)






#### MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)







#### PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)





#### PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)









# LUNA QUDO<sup>™</sup> PENDANT


### DIRECT

PN	SIZE (LXW)	LUMENS	WATTAGE
	24D	2843	32
	36D	4264	48
04111100	48D	5683	65
941LUQP	60D	7096	80
	72D	8229	96
	84D		

#### **IES INDOOR REPORT**

PHOTOMETRIC FILENAME: 941LUQ 24 D 3500K.IES

#### **POLAR GRAPH**



MAXIMUM CANDELA = 1127.86 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 0 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD.) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) # 3 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) # 4 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (0) (THROUGH MAX. CD.)

LUMINAIRE LUMENS	2843
TOTAL LUMINAIRE EFFICIENCY	55%
LUMINAIRE EFFICACY RATING	89
TOTAL LUMINAIRE WATTS	32


### **INDIRECT / DIRECT**

PN	SIZE (LXW)	LUMENS	WATTAGE
941LUQP	24ID	5478	64
	36ID	8296	96
	48ID	11243	132
	60ID	13926	160
	72ID	16263	192
	84ID	19475	224

#### **IES INDOOR REPORT**

#### PHOTOMETRIC FILENAME: 941LUQ 24 ID 3500K.IES

#### **POLAR GRAPH**




MAXIMUM CANDELA = 1148.09 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 0 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) # 3 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) # 4 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (0) (THROUGH MAX. CD.)

LUMINAIRE LUMENS	5478
TOTAL LUMINAIRE EFFICIENCY	54%
LUMINAIRE EFFICACY RATING	86
TOTAL LUMINAIRE WATTS	64

### **TMS**LIGHTING



# LUNA QUDO<sup>™</sup>PENDANT



DISPLAYED FINISHES DIFFER BETWEEN SCREENS AS WELL AS PRINTERS AND MAY NOT ACCURATELY DEPICT COLOR.



