LUNA QUDOTM PENDANT


PROJECT:	
TYPE:	
QUANTITY:	







PN: 941LUQP

	<u> </u>
ILLUMINATION	2,843 - 19,475 LUMENSDIRECT OR INDIRECT/DIRECTLED 90CRI
APPLICATION	DIRECT OR DIRECT/INDIRECT PENDANT MOUNTINDOOR RATED
DIMENSION	 24", 36", 48", 60", 72", 84" SIZES (61cm, 92cm, 122cm, 153cm, 183cm, and 213cm PROFILE: 1"W X 2.625"H (2.54cm X 6.6675cm)
ELECTRICAL	• 120 - 277V • 10KV SURGE SUPRESSION
DIFFUSERS	HIGH EFFICIENCY ACRYLIC
MOUNTING	 120" (304.8cm) BLACK OR WHITE DROP CORD WITH AIRCRAFT CABLES 120" (304.8cm) POWER OVER SUSPENSION
LED DRIVER	CANOPY OR REMOTE MOUNT
CONSTRUCTION	ALUMINUM
FINISHES	 AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES CUSTOM RAL FINISHES AVAILABLE
DIMMING	 0 - 10V (1%) DIMMING (120-277V) LINE VOLTAGE/TRIAC/ELV (120V ONLY) LUTRON HI-LUME (1%) DIMMING (120-277V)
WEIGHT	• 17 LBS MINIMUM, 47 LBS MAXIMUM









LUNA QUDOTM PENDANT

PROJECT:	
TYPE:	
QUANTITY:	

941LU0P			_	_	_		_	_	_
J	1	2	3	4	5	6	7	8	9

1.	DIRECT						
LENGTH	2D	3D	4D	5D	6D	7D	
LENGIN	24" (61cm)	36" (92cm)	48" (122cm)	60" (153cm)	72" (183cm)		
LED (W)	32W	32W 48W		80W	96W		
LUMENS	2843 4264		5683	7096	8229		
	INDIRECT/DIRECT						
LENGTH	2ID	3ID	4ID	5ID	6ID	7ID	
LENGIH	24" (61cm)	36" (92cm)	48" (122cm)	60" (153cm)	72" (183cm)	84" (213cm)	
LED (W)			96W 132W 160W		192W	224W	
LUMENS			11243	13926	16263	19475	
2	u		M			0.	

2.	Н	М	L	C:
OUTPUT	100% LUMENS	75% LUMENS	50% LUMENS	[CUSTOM]% LUMENS

3.	30K	35K	40K
LED CCT	3000	3500	4000

4.	S	D
CIRCUITS	SINGLE	DUAL

5.	MMCD	MMRM	PSCD	PSRM
MOUNTING	MULTIPLE CABLES AND CANOPY DRIVER	MULTIPLE CABLES AND REMOTE DRIVER	SINGLE POINT WITH CANOPY DRIVER	SINGLE POINT WITH REMOTE DRIVER

6.	ВС	wc	POS
CORD	BLACK DROP CORD WITH AIRCRAFT CABLES	WHITE DROP CORD WITH AIRCRAFT CABLES	POWER OVER SUSPENSION (SILVER ONLY) (UP TO 60° ONLY) (NOT APPLICABLE FOR MMCD COMBINATION)

COND	BEACK BROF CORD WITH AIRCRAFT CABLES	WHITE BROF CORD WITH AIRCRAFT CABLES	(NOT APPLICABLE FOR MMCD COMBINATION)
7.	FLAT		DOM
DIEELIGER	ELAT DIEELIGER		DOME DIEFLISER

8.	ADDITIONAL AND PREMIUM FINISHES	F04	F05	F15	F16	F09	F31	F18
FINISH	AVAILABLE. SEE FINISHES CHART	MATTE WHITE	GLOSS WHITE	MATTE BLACK	GLOSS BLACK	PEWTER	SILVER METALLIC	SATIN ALUMINUM


9.	DIML	DIME	DIMV
DIMMING	0-10V (1%) (120-277V)	LUTRON HI-LUME (1%) (120-277V) (UP TO 48" ONLY)	LINE VOLTAGE/TRIAC/ELV (120V ONLY)


NOTE: SOME OPTIONS MAY NOT BE COMPATIBLE WITH OTHERS. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT TMS LIGHTING FOR UPDATED SPECIFICATIONS.








LUNA QUDO M PENDANT















SIZE	ACTUAL SIZE	MOUNTING POINTS	MINIMUM DISTANCE	CANOPY SIZE		NUMBER	WEIGHT	SECTIONS
SIZE				MMCD	PSCD - PSRM	OF CANOPY	(POUNDS - LBS)	SECTIONS
24	24.5"	4	30"	10"	10"	1(D)/ 1(ID)	17	1
36	36.5"	4	50"	10"	10"	1(D)/ 1(ID)	21	1
48	48.5"	4	75"	10"	10"	1(D)/ 1(ID)	25	1
60	60.3"	4	90"	10"	10"	1(D)/ 1(ID)	37	1
72	72.3"	4	110"	12"	12"	1(D)/ 1(ID)	42	1
84	84"	4	N/A	12"	N/A	1(D)/ 1(ID)	47	1


LUNA QUDO THE PENDANT

POS (POWER OVER SUSPENSION)

MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)




PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)





PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)







LUNA QUDO M PENDANT


DROP CORD


MMCD COMBINATION (MUTIPLE CABLES, CANOPY MOUNT DRIVER)






MMRM COMBINATION (MUTIPLE CABLES, REMOTE MOUNT DRIVER)







PSCD COMBINATION (SINGLE POINT, CANOPY MOUNT DRIVER)





PSRM COMBINATION (SINGLE POINT, REMOTE MOUNT DRIVER)





LUNA QUDOTM PENDANT


DIRECT

PN	SIZE (LXW)	LUMENS	WATTAGE
	24D	2843	32
	36D	4264	48
941LUQP	48D	5683	65
941LUQP	60D	7096	80
	72D	8229	96
	84D		

IES INDOOR REPORT

PHOTOMETRIC FILENAME: 941LUQ 24 D 3500K.IES

POLAR GRAPH



MAXIMUM CANDELA = 1127.86 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 0 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD.) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) # 3 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270)

TOTAL LUMINAIRE WATTS

4 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (0) (THROUGH MAX. CD.)

LUMINAIRE LUMENS 2843 **TOTAL LUMINAIRE EFFICIENCY** 55% **LUMINAIRE EFFICACY RATING** 89


INDIRECT / DIRECT

PN	SIZE (LXW)	LUMENS	WATTAGE
	24ID	5478	64
	36ID	8296	96
941LUQP	48ID	11243	132
941LUQP	60ID	13926	160
	72ID	16263	192
	84ID	19475	224

IES INDOOR REPORT

PHOTOMETRIC FILENAME: 941LUQ 24 ID 3500K.IES

POLAR GRAPH



MAXIMUM CANDELA = 1148.09 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 0 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) # 3 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) # 4 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (0) (THROUGH MAX. CD.)

32

LUMINAIRE LUMENS	5478
TOTAL LUMINAIRE EFFICIENCY	54%
LUMINAIRE EFFICACY RATING	86
TOTAL LUMINAIRE WATTS	64

LUNA QUDO THE PENDANT

FINISHES



F04 MATTE WHITE



F05 GLOSS WHITE



F15 MATTE BLACK



F16 GLOSS BLACK



F09 PEWTER



F31 SILVER METALLIC



F18 SATIN ALUMINUM



F21 ARCH BRONZE

PREMIUM FINISHES



RAL CUSTOM (RAL #)



F40 BUBBLE PINK



F10 FIRE RED



F41 ELECTRIC PURPLE



F08 MIDNIGHT BLUE



F39 AQUA BLUE



F13 FOREST GREEN



F38 MEADOW GREEN



F45 COPPER METALLIC



F06 CLAY BROWN



F11 CITRUS ORANGE



F28 DARK CHAMPAGNE



F22 HARVEST GOLD



F14 SUNSHINE YELLOW



F33 PYRITE BRONZE



F07 ZEUS BROWN



F32 BRONZE METALLIC



F26 MELTED COPPER



F25 MELTED GOLD



F24 MELTED PLATINUM



F43 FAUX GOLD



F42 FAUX CHROME

DISPLAYED FINISHES DIFFER BETWEEN SCREENS AS WELL AS PRINTERS AND MAY NOT ACCURATELY DEPICT COLOR.

