

ORBITA™ O CEILING

PROJECT: _____

TYPE: _____



QUANTITY: _____



PN: 9910ROC

ILLUMINATION	• 7,458 - 18,363 LUMENS • LED 90CRI
APPLICATION	• INDOOR RATED
DIMENSION	• 36", 48", 60", 84" DIA. (91cm, 122cm, 152cm, and 213cm) • PROFILE: 1.68"W X 2.73"H (4.2cm X 6.93cm)
ELECTRICAL	• 120 - 277V • 10KV SURGE SUPPRESSION
DIFFUSERS	• HIGH EFFICIENCY ACRYLIC
MOUNTING	• CANOPY OR REMOTE MOUNT
CONSTRUCTION	• ALUMINUM
FINISHES	• AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES • CUSTOM RAL FINISHES AVAILABLE
DIMMING	• 0 - 10V (1%) DIMMING (120-277V) • LINE VOLTAGE/TRIAC/ELV (120V ONLY) • LUTRON HI-LUME (1%) DIMMING (120-277V)
WEIGHT	• 20 LBS MINIMUM, 40 LBS MAXIMUM

CROSS SECTION



TMSLIGHTING

INDOOR



ORBITA™ O CEILING



PROJECT: _____

TYPE: _____

QUANTITY: _____

9910ROC

1 2 3 4 5 6

1.	36	48	60	72	84
DIA (INCH)	36"	48"	60"	72"	84"
LED (W)	71	97	121	146	177
LUMEN	7458	10096	12568	15185	18363

2.	H	M	L	C: _____
OUTPUT	100% LUMENS	75% LUMENS	50% LUMENS	[CUSTOM]% LUMENS

3.	30K	35K	40K
CCT	3000	3500	4000

4.	CD	RM
DRIVER	CANOPY MOUNT	REMOTE MOUNT

5.	ADDITIONAL AND PREMIUM FINISHES AVAILABLE. SEE FINISHES CHART	F04	F05	F15	F16	F09	F31	F18
FINISH		MATTE WHITE	GLOSS WHITE	MATTE BLACK	GLOSS BLACK	PEWTER	SILVER METALLIC	SATIN ALUMINUM


6.	DIML	DIME	DIMV
DIMMING	0-10V (1%) (120-277V)	LUTRON HI-LUME (1%) (120-277V) (UP TO 60" ONLY)	LINE VOLTAGE/TRIAC/ELV (120V ONLY)

NOTE: SOME OPTIONS MAY NOT BE COMPATIBLE WITH OTHERS. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT TMS LIGHTING FOR UPDATED SPECIFICATIONS.

TMSLIGHTING



ORBITA™ O CEILING




SIZES	DIAMETER	MOUNTING POINT	CANOPY SIZE	NUMBER OF CANOPY	WEIGHT (POUNDS - LBS)	SECTIONS
36	36.5"	3	10"	1	20	1
48	47.5"	3	10"	1	25	1
60	59.5"	3	10"	1	30	1
72	72"	4	15"	1	35	1
84	84"	4	15"	1	40	1


1. ONLY FOR PS (SINGLE POINT) MOUNTING OPTION, THIS IS THE MINIMUM DISTANCE FROM CEILING TO THE BOTTOM OF THE FIXTURE
 2. MINIMUM CABLE MOUNTING ANGLE IS 70°

MOUNTING

CANOPY MOUNT DRIVER




REMOTE MOUNT DRIVER



PN (INCH)	LUMENS	WATTAGE
36 (36")	7458	71
48 (48")	10096	97
60 (60")	12568	121
72 (72")	15185	146
84 (84")	18363	177

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 9910ROC 36 35K F05.IES

POLAR GRAPH




MAXIMUM CANDELA = 865.78 - LOCATED AT HORIZONTAL ANGLE = 67.5, VERTICAL ANGLE = 90
 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (67.5 - 247.5) (THROUGH MAX. CD.)
 # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (90) (THROUGH MAX. CD.)

LUMINAIRE LUMENS 7458
TOTAL LUMINAIRE EFFICIENCY 75%
LUMINAIRE EFFECIENCY RATING 105
TOTAL LUMINAIRE WATTS 71

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 9910ROC 84 35K F05.IES

POLAR GRAPH



MAXIMUM CANDELA = 2318.86 - LOCATED AT HORIZONTAL ANGLE = 45, VERTICAL ANGLE = 90
 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) (THROUGH MAX. CD.)
 # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (90) (THROUGH MAX. CD.)

LUMINAIRE LUMENS 18363
TOTAL LUMINAIRE EFFICIENCY 74%
LUMINAIRE EFFECIENCY RATING 104
TOTAL LUMINAIRE WATTS 177

FINISHES



F04
MATTE
WHITE



F05
GLOSS
WHITE



F15
MATTE
BLACK



F16
GLOSS
BLACK



F09
PEWTER



F31
SILVER
METALLIC



F18
SATIN
ALUMINUM



F21
ARCH
BRONZE

PREMIUM FINISHES



RAL
CUSTOM
(RAL #)



F40
BUBBLE
PINK



F10
FIRE
RED



F41
ELECTRIC
PURPLE



F08
MIDNIGHT
BLUE



F39
AQUA
BLUE



F13
FOREST
GREEN



F38
MEADOW
GREEN



F45
COPPER
METALLIC



F06
CLAY
BROWN



F11
CITRUS
ORANGE



F28
DARK
CHAMPAGNE



F22
HARVEST
GOLD



F14
SUNSHINE
YELLOW



F33
PYRITE
BRONZE



F07
ZEUS
BROWN



F32
BRONZE
METALLIC



F26
MELTED
COPPER



F25
MELTED
GOLD



F24
MELTED
PLATINUM



F44
FAUX
COPPER



F43
FAUX
GOLD



F42
FAUX
CHROME

NOTE: DISPLAYED FINISHES DIFFER BETWEEN SCREENS AS WELL AS PRINTERS AND MAY NOT ACCURATELY DEPICT COLOR.