# ROUND TOP<sup>TM</sup> BOLLARD

PROJECT:	
TYPE:	
OLIANITITY	



### PN: RTB

1 14. IVID	
APPLICATION	SURFACE MOUNT     OUTDOOR RATED
DIMENSION	• 6"D OR 8"D X 36"H OR 42"H (15CM OR 20CM X 91CM OR 107CM)
ILLUMINATION	<ul><li>DIFFUSE</li><li>LED 90CRI</li><li>627 - 1,225 LUMENS</li></ul>
ELECTRICAL	<ul><li>120V, 277V AND 347V</li><li>10kA SURGE SUPRESSION STANDARD</li></ul>
DIFFUSERS	HIGH EFFICIENCY ACRYLIC
MOUNTING	<ul> <li>FIXED SURFACE, MOUNT TO A SOLID FOUNDATION WITH PLATE AND ANCHOR BOLTS (SUPPLIED)</li> </ul>
CONSTRUCTION	• ALUMINUM
FINISHES	<ul> <li>AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES</li> <li>CUSTOM RAL FINISHES AVAILABLE</li> </ul>



# ROUND TOP<sup>™</sup> BOLLA

BO	 Λ		
H	 Α	H	1

PROJECT:	
TYPE:	
OUANTITY:	

RTB							
	1	2	3	4	5	6	7

1.	636	642	836	842
HEIGHT	6"DIA X 36"H (15CM X 92CM) 6"DIA X 42"H (15CM X 107CM)		8"DIA X 36"H (20CM X 92CM)	8"DIA X 42"H (20CM X 107CM)
2.				
ILLUMINATION <sup>1</sup>	14LED	19LED	14LED	19LED
LED (W)	14W	19W	14W	19W
LUMENS	784	1041	922	1225

3.	30K	35K	40K
LED CCT	3000K	3500K	4000К
4.	120	277	347

5.	F04	F05	F09	F15	F16	F21	F24	F25	F26	F31
	MATTE WHITE	GLOSS WHITE	PEWTER	MATTE BLACK	GLOSS BLACK	ARCH BRONZE	MELTED PLATINUM	MELTED GOLD	MELTED COPPER	SILVER METALLIC
FINISH	F32	F33	RAL							
	BRONZE METALLIC	PYRITE BRONZE	CUSTOM (SPECIFY)							


6.		ЕМ	EMC
EMERGENCY <sup>2</sup>	NONE	INTEGRAL	INTEGRAL COLD PACK

7.		LV6	LV6AN <sup>3</sup>	LV8	LV8AN <sup>3</sup>
LOUVER	NONE	WHITE, ALUMINUM, 6"	ANODIZED ALUMINUM, 6"	WHITE, ALUMINUM, 8"	ANODIZED ALUMINUM, 8"


<sup>1. 10</sup>W AT 90 MINUTES. EMERGENCY OPTION IS ONLY AVAILABLE IN 120 - 277V SYSTEMS

# ROUND TOP<sup>™</sup> BOLLARD

#### **ANODIZED ALUMINUM REFLECTOR**



### **LOUVER OPTION**



**CUSTOM** 

IOTE: THIS FIXTURE CAN BE CUSTOMIZE, DIMENSION, LAMP TYPES, ENCLOSURE, AND COLOR CAN BE MODIFIED TO SUIT YOUR LIGHTING AND ARCHITECTURAL REQUIREMENTS. CONTACT YOUR LOCAL REPRESENTATIVE FOR MORE DETAIL SENTENCE OF THE PROPERTY OF THE PROPE

## ROUND TOP™ BOLLARD

### **DIFFUSE**

PN	SIZE (DIA)	ILLUMINATION	LOUVER	LUMENS	WATTAGE
		LV6 AN	627	14	
	6	14 LED	LV6	627	14
RTB				784	14
KIB		19 LED		1041	19
		14 LED		922	14
	•	19 LED		1225	19


**IES INDOOR REPORT** 

PHOTOMETRIC FILENAME: RTB 8 19LED.IES

**IES INDOOR REPORT** 


PHOTOMETRIC FILENAME: RTB6 14LED LV6 AN.IES

#### **POLAR GRAPH POLAR GRAPH**



MAXIMUM CANDELA = 140.892 LOCATED AT HORIZONTAL ANGLE = 22.5, VERTICAL ANGLE = 50 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180)

627
36%
45
14



MAXIMUM CANDELA = 282.21 LOCATED AT HORIZONTAL ANGLE = 180, VERTICAL ANGLE = 15 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) # 3 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (90)

LUMINAIRE LUMENS	1225
TOTAL LUMINAIRE EFFICIENCY	NA
LUMINAIRE EFFICACY RATING	53
TOTAL LUMINAIRE WATTS	23

## ROUND TOP™ BOLLARD

### **AVAILABLE FINISHES**



F04 MATTE WHITE



F05 GLOSS WHITE



F09 PEWTER



F15 MATTE BLACK



F16 GLOSS BLACK



F21 ARCH BRONZE



F24 MELTED PLATINUM



F25 MELTED GOLD



F26 MELTED COPPER



F31 SILVER METALLIC



F32 METALLIC BRONZE



F33 PYRITE BRONZE



RAL CUSTOM COLOR (RAL #)