SERENITYTM PENDANT

PROJECT:	
TYPE:	
OLIANITITY.	



PN: 820SI

APPLICATION	PENDANT MOUNTINDOOR RATED	
DIMENSION	• 24", 30", 36", 48" (61CM, 76CM, 91CM, 122CM)	
ILLUMINATION	DIFFUSE LED 90CRI	
ELECTRICAL	120V, 277V AND 347V10kA SURGE SUPRESSION STANDARD	
DIFFUSERS	HIGH EFFICIENCY ACRYLIC	
MOUNTING	STEM MOUNT	
CONSTRUCTION	• STEEL	
FINISHES	 AVAILABLE IN SEVERAL TMS PLATED, AND POWDER COATED FINISHES CUSTOM RAL FINISHES AVAILABLE 	
DIMMING	• 0 - 10V STANDARD DIMMING (1%)	
WEIGHT	• 36 LBS MAXIMUM	





SERENITYTM PENDANT

PROJECT:	
TYPE:	
QUANTITY:	

820SI								
0_00	1	2	3	4	5	6	7	8

1.	24	30 36		48
DIAMETER	24"D X 24"H (61CM X 61CM)	30"D X 24"H (76CM X 61CM)	36"D X 30"H (91CM X 76CM)	48"D X 36"H (122CM X 92CM)

2.	40LED	60LED	75LED	40IN4	60IN6
ILLUMINATION	40LED	60LED	75LED	40IN4	60IN6
LED (W)	40W	240	240	160	300
LUMENS	24" : 3370	36" : 5108	48" : 5875	24", 36" ONLY	40" ONLY

3.	****	30К	35К	40K
LED CCT	NONE	3000	3500	4000

4.	120	277	347
VOLTAGE	120V	277V	347V


5.	SN	СН	ВС	AC	AB	SB	PB	F04	F05	F16
	SATIN NICKEL	CHROME	BLACK CHROME	ANTIQUE COPPER	ANTIQUE BRASS	SATIN BRASS	POLISHED COPPER	MATTE WHITE	GLOSS WHITE	GLOSS BLACK
FINISH	F33	RAL								
	PYRITE BRONZE	CUSTOM (SPECITY)								


6.	OP
DIFFUSER	OPAL - WHITE ACRYLIC


7.		DIML
DIMMING	NONE	LED DIMMING (0 - 10V, CURRENT - SINKING)

8.	CD	OD
DUST COVER	CLEAR DUST COVER	OPAL - WHITE DUST COVER

SERENITY PENDANT















BOTTOM



CUSTOM

...
NOTE: THIS FIXTURE CAN BE CUSTOMIZE. DIMENSION, LAMP TYPES, ENCLOSURE, AND COLOR CAN BE MODIFIED TO SUIT YOUR LIGHTING AND ARCHITECTURAL REQUIREMENTS. CONTACT YOUR LOCAL REPRESENTATIVE FOR MORE DETAILS: https://tmsiighting.com/sales-agents.html

820SI


SERENITY PENDANT

PN	WATTAGE	LUMENS	WEIGHT
24	41	3370	14LBS
36	59	5108	25LBS
48	79	5875	36LBS

IES INDOOR REPORT

PHOTOMETRIC FILENAME: 820SI 24 40LED 35K F05.IES

POLAR GRAPH




Maximum Candela = 859.72 Located At Horizontal Angle = 180, Vertical Angle = 10 # 1 - Vertical Plane Through Horizontal Angles (180 - 0) (Through Max. Cd.) # 2 - Horizontal Cone Through Vertical Angle (10) (Through Max. Cd.)

LUMINAIRE LUMENS
TOTAL LUMINAIRE EFFICIENCY
LUMINAIRE EFFICACY RATING
TOTAL LUMINAIRE WATTS

IES INDOOR REPORT

PHOTOMETRIC FILENAME: 820SI 48 75LED 35K F05.IES

POLAR GRAPH



Maximum Candela = 2479.53 Located At Horizontal Angle = 157.5, Vertical Angle = 5 # 1 - Vertical Plane Through Horizontal Angles (157.5 - 337.5) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (5) (Through Max. Cd.)

3370	LUMINAIRE LUMENS	5875
54%	TOTAL LUMINAIRE EFFICIENCY	54%
82	LUMINAIRE EFFICACY RATING	75
41	TOTAL LUMINAIRE WATTS	79

SERENITYTM PENDANT

AVAILABLE FINISHES



SN SATIN NICKEL



CH CHROME



BC BLACK CHROME



AC ANTIQUE COPPER



AB ANTIQUE BRASS



SB SATIN BRASS



PB POLISHED BRASS



F04 MATTE WHITE



F05 GLOSS WHITE



F16 GLOSS BLACK



F33 PYRITE BRONZE



RAL CUSTOM COLOR (RAL #)

