

PROJECT: _____

TYPE: _____

QUANTITY: _____



PN: 1

APPLICATION	• WALL MOUNT • INDOOR OR OUTDOOR RATED
DIMENSION	• 10" DIA (25CM)
ILLUMINATION	• DIRECT • LED 90CRI • 1,157 - 1,863 LUMENS
ELECTRICAL	• 120V, 277V AND 347V • 10kA SURGE SUPPRESSION STANDARD
DRIVER	• WALL MOUNT (INTEGRAL) • REMOTE MOUNT (INDOOR OR OUTDOOR)
DIFFUSERS	• CLEAR OR FROSTED GLASS GLOBE
MOUNTING	• WALL, MOUNTED OVER A 4"(10CM) J-BOX
CONSTRUCTION	• ALUMINUM W/ STAINLESS STEEL MOUNT
FINISHES	• AVAILABLE IN ANODIZED, BRUSHED, AND SEVERAL TMS POWDER COATED FINISHES • CUSTOM RAL FINISHES AVAILABLE
DIMMING	• 0 - 10V STANDARD DIMMING
WEIGHT	• 6.5 LBS.





PROJECT: _____

TYPE: _____

QUANTITY: _____

1 - 1 2 3 4 5 6 7 8 9 10

1	ILLUMINATION									
	100IN ¹		15LED		16LED ¹			19LED		
LED (W)	100W		15W		16W PAR38 E26 MED. BASE, 40°			19W		
LUMENS	1157		1396		1400 LUMENS (27/30/35/40/50K) REFER TO PAGE 6			1863		
2.	----		30K		35K			40K		
LED CCT	NONE		3000K		3500K			4000K		
3.	120			277				347		
VOLTAGE	120V			277V				347V		
4.	----		WM		N1			N4		
DRIVER	NONE		WALL MOUNT (INTEGRAL)		REMOTE INDOOR MOUNT (NEMA 1)			REMOTE OUTDOOR MOUNT (NEMA 4)		
5.	F04	F05	F15	F16	F09	F31	F18	F06	F07	F08
FINISH ²	MATTE WHITE	GLOSS WHITE	MATTE BLACK	GLOSS BLACK	PEWTER	SILVER METALLIC	SATIN ALUMINUM	CLAY BROWN	ZEUS BROWN	MIDNIGHT BLUE
	F10	F11	F13	F14	F21	F22	F24	F25	F26	F28
	FIRE RED	CITRUS ORANGE	FOREST GREEN	SUNSHINE YELLOW	ARCH. BRONZE	HARVEST GOLD	MELTED PLATINUM	MELTED GOLD	MELTED COPPER	DARK CAMPAGNE
	F32	F33	F38	F39	F40	F41	F42	F43	F44	F45
	BRONZE METALLIC	PYRITE BRONZE	MEADOW GREEN	AQUA BLUE	BUBBLE PINK	ELECTRIC PURPLE	FAUX CHROME	FAUX GOLD	FAUX COPPER	COPPER METALLIC
	RAL	BR	AN							
	CUSTOM (SPECIFY RAL)	BRUSHED ALUMINUM	ANODIZED	ADDITIONAL AND PREMIUM FINISHES AVAILABLE. SEE FINISHES CHART						
6.	----					DIML				
DIMMING	NONE					LED DIMMING (0 - 10V, CURRENT - SINKING)				
7.	----		EM		EMC		EMR		EMCR	
EMERGENCY ³	NONE		INTEGRAL		INTEGRAL COLD PACK		REMOTE		REMOTE COLD PACK	
8.	----			G1				G2		
GLOBE/ ⁴ LENS	NONE			CLEAR, ELONGATED GLOBE				FROSTED GLOBE		
9.	----				W10					
WIRE GUARD	NONE				10" WIRE GUARD					
10.	----					AK				
ACCESSORIES	NONE					AIMING KNUCKLE				

1. INCANDESCENT SYSTEMS, AND 16W LED PAR 38 LAMPS, USE A MEDIUM BASE SOCKET (E26). SEE PAGE 6 FOR MORE DETAILS PERTAINING TO THE 16W LED PAR 38 LAMPS.


2. REFLECTOR INSIDE IS FINISHED WHITE

3. 10W AT 90 MINUTES. EMERGENCY OPTION IS ONLY AVAILABLE IN 120 - 277V SYSTEMS

4. GLOBES ARE NOT AVAILABLE WITH THE 17W LED PAR 38 LAMPS

NOTE: SOME OPTIONS MAY NOT BE COMPATIBLE WITH OTHERS. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT TMS LIGHTING FOR UPDATED SPECIFICATIONS.

1



CUSTOM

NOTE: THIS FIXTURE CAN BE CUSTOMIZE. DIMENSION, LAMP TYPES, ENCLOSURE, AND COLOR CAN BE MODIFIED TO SUIT YOUR LIGHTING AND ARCHITECTURAL REQUIREMENTS. CONTACT YOUR LOCAL REPRESENTATIVE FOR MORE DETAILS: <https://tmslighting.com/sales-agents.html>

TMSLIGHTING


DIRECT

PN	ILLUMINATION	LUMENS	WATTAGE
1	100IN	1157	100
	15LED	1396	15
	19LED	1863	19

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 1 15LED 35K WM F05.IES

POLAR GRAPH



MAXIMUM CANDELA = 488.16 LOCATED AT HORIZONTAL ANGLE = 45, VERTICAL ANGLE = 10
 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) (THROUGH MAX. CD.)
 # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (10) (THROUGH MAX. CD.)

LUMINAIRE LUMENS

1396

TOTAL LUMINAIRE EFFICIENCY

99%

LUMINAIRE EFFICACY RATING

93


TOTAL LUMINAIRE WATTS

15

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 1 19LED 35K WM F05.IES

POLAR GRAPH



MAXIMUM CANDELA = 645.67 LOCATED AT HORIZONTAL ANGLE = 45, VERTICAL ANGLE = 15
 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (45 - 225) (THROUGH MAX. CD.)
 # 2 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (15) (THROUGH MAX. CD.)

LUMINAIRE LUMENS

1863

TOTAL LUMINAIRE EFFICIENCY

99%

LUMINAIRE EFFICACY RATING

93

TOTAL LUMINAIRE WATTS

20

FINISHES



PREMIUM FINISHES



PREMIUM MATERIALS



1: FINISHES IS APPLIED TO THE INTERIOR AND EXTERIOR OF THE FIXTURE.

2: MATERIALS ARE CONSISTENT (INTERIOR & EXTERIOR). STEMS AND CANOPIES WILL BE F16 GLOSS BLACK.

NOTE: ALL FINISHES NOT MARKED WITH NOTATION (1) ARE APPLIED TO THE EXTERIOR ONLY. THE INTERIOR WILL BE F05 GLOSS WHITE.

MATTE FINISHES AVAILABLE. CONSULT FACTORY.

FINISHES ARE SUBJECT TO AVAILABILITY AND MAY NOT BE APPLICABLE TO ALL FIXTURES OR FOR QUICKSHIP.

DISPLAYED FINISHES DIFFER BETWEEN SCREENS AS WELL AS PRINTERS AND MAY NOT ACCURATELY DEPICT COLOR.

16W LED PAR 38 MED BASE, 40° (SUPPLIED)

HD-PAR/I90/5CCT



FEATURES & BENEFITS

5 FIELD SELECTABLE CCT'S (27/30/35/40/50K)

HIGH CRI (90+)


GLASS LENS

25,000 HRS AVERAGE LIFE

WET LOCATION RATED

DIMMABLE

DIMENSIONAL DRAWING



MODEL NUMBER	WATTAGE (W)	BASE	VOLTAGE (V)	HOUR RATING	BEAM ANGLE	INITIAL LUMENS(LM)	CCT(K)	CRI	ENCLOSED FIXTURE APPLICATION	WET LOCATION	M.O.D. (INCH)	M.O.L. (INCH)
16W LED	16	E26	120	25,000	40°	1400	27/30/35/40/50	90	NO	YES	4.8	5.31