SQUARE TOPTM BOLLARD

PROJECT:	
TYPE:	
OLIA NITITY	



PN: STB

<u> </u>	
APPLICATION	SURFACE MOUNTINDOOR RATED
DIMENSION	• 8"SQ X 36"H OR 42"H (20CM X 91CM OR 107CM)
ILLUMINATION	DIFFUSELED 90CRI901 - 1,200 LUMENS
ELECTRICAL	120V, 277V AND 347V10kA SURGE SUPRESSION STANDARD
DIFFUSERS	HIGH EFFICIENCY ACRYLIC
MOUNTING	 FIXED SURFACE, MOUNT TO A SOLID FOUNDATION WITH PLATE AND ANCHOR BOLTS (SUPPLIED)
CONSTRUCTION	• ALUMINUM
FINISHES	 AVAILABLE IN SEVERAL TMS POWDER COATED FINISHES CUSTOM RAL FINISHES AVAILABLE



PROJECT:	
TYPE:	
QUANTITY:	

STB							_
U.	1	2	3	4	5	6	7

1.	836	842	
HEIGHT	8"DIA X 36"H (20CM X 92CM)	8"DIA X 42"H (20CM X 107CM)	
2.			
ILLUMINATION	14LED	19LED	
LED (W)	14W	19W	
LUMENS	901	1200	


ა.	30K	35K	40K
LED CCT	3000K	3500K	4000K
4.	120	277	347

I	5.	F04	F05	F09	F15	F16	F21	F24	F25	F26	F31
		MATTE WHITE	GLOSS WHITE	PEWTER	MATTE BLACK	GLOSS BLACK	ARCH BRONZE	MELTED PLATINUM	MELTED GOLD	MELTED COPPER	SILVER METALLIC
ı	FINISH	F32	F33	RAL							
ı		BRONZE METALLIC	PYRITE BRONZE	CUSTOM (SPECIFY)							


6		EM	EMC	
EMERGENCY ¹	NONE	INTEGRAL	INTEGRAL COLD PACK	
7.	-	LV8	LV8AN	

^{1. 10}W AT 90 MINUTES. EMERGENCY OPTION IS ONLY AVAILABLE IN 120 - 277V SYSTEMS

ANODIZED ALUMINUM REFLECTOR



WHITE ALUMINUM LOUVER OPTION



DIFFUSE

PN	ILLUMINATION	LUMENS	WATTAGE
стр	14 LED	901	14
STB	19 LED	1200	19


IES INDOOR REPORT

PHOTOMETRIC FILENAME: STB 8 14LED.IES

IES INDOOR REPORT

PHOTOMETRIC FILENAME: STB 8 19LED.IES

POLAR GRAPH




), VERTICAL ANGLE = 60 ROUGH MAX. CD.)

MAX. CD.)

MAXIMUM CANDELA = 190.65 LOCATED AT HOR # 1 - VERTICAL PLANE THROUGH HORIZONTAL AN # 2 - VERTICAL PLANE THROUGH HORIZONTAL AN # 3 - HORIZONTAL CONE THROUGH VERTICAL ANG	IZONTAL ANGLE = 0, IGLES (0 - 180) (THRO IGLES (90 - 270) IGLE (60) (THROUGH M
LUMINAIRE LUMENS	
TOTAL LUMINAIRE EFFICIE	ENCY
LUMINAIRE EFFICACY RAT	ING
TOTAL LUMINAIRE WATTS	

POLAR GRAPH



MAXIMUM CANDELA = 254.53 LOCATED AT HORIZONTAL ANGLE = 0, VERTICAL ANGLE = 60 # 1 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (0 - 180) (THROUGH MAX. CD.) # 2 - VERTICAL PLANE THROUGH HORIZONTAL ANGLES (90 - 270) # 3 - HORIZONTAL CONE THROUGH VERTICAL ANGLE (60) (THROUGH MAX. CD.)

901	LUMINAIRE LUMENS	1200
NA	TOTAL LUMINAIRE EFFICIENCY	NA
58	LUMINAIRE EFFICACY RATING	53
16	TOTAL LUMINAIRE WATTS	22

AVAILABLE FINISHES



F04 MATTE WHITE



F05 GLOSS WHITE



F09 PEWTER



F15 MATTE BLACK



F16 GLOSS BLACK



F21 ARCH BRONZE



F24 MELTED PLATINUM



F25 MELTED GOLD



F26 MELTED COPPER



F31 SILVER METALLIC



F32 METALLIC BRONZE



F33 PYRITE BRONZE



RAL CUSTOM COLOR (RAL #)